

CONVEYOR DISHWASHER WITH PRE-WASH

COLIT31112



PRODUCT FEATURES

These machines are characterised by their compact external dimensions, thanks to the rinsing system being incorporated in the wash module. The user interface is the acclaimed LED ProSmart, which provides simple and intuitive control of machine functions. Another fundamental feature is the low water consumption, which on some machines is as low as 1,1 litres per rack. All models are equipped as standard with the autotimer and rinse economizer, as well as integral steel filters in the wash tank. A wide choice of optional accessories, tables and roller ways means that the machine can be adapted perfectly to any installation requirements.

3 Standard programmes (for glasses, self-cleaning and tank water changing):

ProSpeed programme - for fresh, light soiling.
ProFessional programme - for general use.
ProTemp programme - with a high-temperature water rinse.

4 Specialised programmes:

ProWater programme - specially for osmosis water.
ProPlates programme - for plates.
ProClean - Self-cleaning cycle with high-pressure jets for machines programme and automatic drain.
ProDrain: automatic tank draining.

DuoFlow pump - 2 outlets, with one outlet connected directly to the upper arm and the other to the lower arm, this system eliminates the loss of pressure caused by dividing the flow.

HiTech wash arms - made from (30% fibreglass, 30% talcum microparticles, 40% organic resin).

UltraRinse rinse arm - geometry ensures that the water is used more effectively and efficiently, thereby helping to minimise consumption.

EnergySaving system - 25% less energy consumption than competitors.

HotWash heating system - shares the electrical power between two independent heating elements so as to allow numerous repeated wash cycles and constant heating of the tank (results in 10°C higher temperature during repeated wash cycles, shorter wash time and drying time, lower detergent consumption and consequently lower costs.)

ThermoStop rinse control - ensures constant temperature at the start of the rinse cycle (minimum water consumption is 1,5 litres/cycle).

SmartScreen user interface.

TECHNICAL SPECIFICATIONS

Model	LxDxH (mm)	Door Opening(cm)	Power Hot Water(kW)	Power Cold Water(kW)	Power Heat Plus(kW)	Water Consumption(Ltr/hr)	Electrical Connection
COLIT31112	1968x770x615	45	30.2	45.2	47.9	320	230V/1pH/50-60Hz