


DISHWASHER: UNDERCOUNTER

COLIT3611MD



PRODUCT FEATURES

- Full double-skin construction with stratified double-skin construction for the sides of the wash chamber.
- Full double-skin construction for the door.
- The tank has press-moulded bottom and is equipped with a full-width integral surface filter, which, thanks to its large intake size, is virtually unblockable.
- The wash chamber is free of internal pipes and sharp corners.
- Easy to use, reliable and complete, with four soft touch keys and a 4-character LED display with two lateral indicator bars.
- Adjustable tank and boiler temperatures, the dosing of detergent and rinse aid.
- Volumetric rinse - uses ThermoStop to ensure a constant temperature at the start of the rinse cycle.
- Equipped as standard with electronically-controlled peristaltic dosing units for both detergent and rinse aid.
- Equipped as standard with plate rack and a fl at rack, a cutlery container, approved filler hose and drain hose.
- Programmes (for glasses, self cleaning and tank water changing):
- ProSpeed programme - for fresh, light soiling.
- ProFessional programme - for general use.
- ProTemp programme - with high temperature water rinse.
- ProGlass programme - for glass and crystal
- ProWater programme - for osmosis water.
- ProLong programme - continuous wash for dried-on dirt.
- ProEco programme - low temperature for blood and starch.
- ProClean - Self-cleaning cycle with high-pressure jets for machines programme and automatic drain.
- ProDrain: automatic tank draining.
- DuoFlow pump - 2 outlets, with one outlet connected directly to the upper arm and the other to the lower arm, this system eliminates the loss of pressure caused by dividing the flow.
- HiTech wash arms - made from (30% fibreglass, 30% talcum microparticles, 40% organic resin).
- UltraRinse rinse arm - geometry ensures that the water is used more effectively and efficiently, thereby helping to minimise consumption.
- EnergySaving system - 25% less energy consumption than competitors.
- ThermoStop rinse control - ensures constant temperature at the start of the rinse cycle (minimum water consumption is 2 litres/cycle).
- Progressive triple-stage filtration of the tank water with elimination of particles down to a diameter of 0.8 mm.

DISHWASHER: UNDERCOUNTER

COLIT3611MD

TECHNICAL SPECIFICATIONS

Model	LxDxH (mm)	Rack size (mm)	Tank capacity (L)	Boiler capacity (L)	Max. real production (rack/h)	Door/hood opening (mm)	Power (W)	Electric connection
COLIT3611MD	575x605x820	500x500	20	6	20	365	6.800	230V/1ph/50Hz