

ISYTECH36 DISHWASHER

COLIT3611D



PRODUCT FEATURES

Full double-skin construction with stratified double-skin construction for the sides of the wash chamber.
 Full double-skin construction for the door.
 The tank has press-moulded bottom and is equipped with a full-width integral surface filter, which, thanks to its large intake size, is virtually unblockable.
 The wash chamber is free of internal pipes and sharp corners
 Construction Full double-skin construction with stratified double-skin construction for the sides of the wash chamber.
 Full double-skin construction for the door.
 The tank has press-moulded bottom and is equipped with a full-width integral surface filter, which, thanks to its large intake size, is virtually unblockable.
 The wash chamber is free of internal pipes and sharp corners.
 User interface Easy to use, reliable and complete, with four soft touch keys and a 4-character LED display with two lateral indicator bars.
 Carefully chosen combinations of colours and graphic symbols provide a clear indication of the dishwasher status and wash cycle progress at a glance.
 In addition to the operating parameters, such as the temperature of the tank and boiler or the number of cycles completed, the indications provided by the automatic diagnosis system are also displayed. The information is provided in the form of codes, text, or graphic indicators and colours.
 It is possible to adjust the tank and boiler temperatures, the dosing of detergent and rinse aid, while our specialised technicians can modify all the operating parameters of the machine.
 The Versions with four different equipment levels are available, with and without water softener.
 The entire range and the various options can be seen in the table on the next page.
 All models are equipped as standard with electronically-controlled peristaltic dosing units for both detergent and rinse aid.

TECHNICAL SPECIFICATIONS

Model	LxDxH (mm)	Tank Capacity (Litres)	Min-Max Temp. (°C)	Boiler Capacity (Litres)	Power (W)	Mac Capacity (Racks/hr)	Electrical Connection
COLIT3611D	575x600x820	20	15-60	6	3.500	33	400V/ 3ph/ 50Hz