

DOUBLE DOOR UPRIGHT FRIDGE

INFIAG1402



PRODUCT FEATURES

- Energy efficiency class
- Optimized air circulation for a better temperature uniformity
- Doors with hinges for automatic return and permanent pressure during closing.
- Greater precision in temperature control
- LED lighting reducing energetic consumption between 80% and 90% respect to a traditional light bulb
- All the condensing units are 100% tested, in a Helium chamber for the detection of gas leakage.
- Refrigeration: Temperature controller with digital display.
- Automatic evaporation of defrost water.
- Automatic defrost.
- Ventilated condensation system.
- Monoblock refrigeration system.
- Forced draft evaporator with anticorrosion lining.
- Climatic class 4 (30oC, 55%RH).
- Exterior: AISI 430 stainless steel, except doors and control panel, which are made of AISI 304 stainless steel.
- Galvanized steel back.
- Totally injected compact structure
- Adjustable legs up to 200 mm- thermometer is standard.

TECHNICAL SPECIFICATIONS

Model	Dimensions (WxDxH)	Chamber Volume (L)	Temperature Range	Gas charge (gr)	Electrical Connection
IAG1402	1385x800x2133	1340	-2 °C/ +8 °C	400	230 V/ 1 ph/ 50Hz