



### PRI 210 [EL STW AB]

Rotary ironer, electrically heated

With the latest controls and flexible working height.



- Performance 30.0 kg/h\*, roller diameter 210 mm, working width 1000 mm
- Ideal ergonomics – height-adjustable and optional plinth
- State-of-the-art controls – Touch display
- Selection of the most important settings – favourite programmes
- Perfect rotary ironing performance – flexibly positioned heater plate

\* With 15 % residual moisture – performance data according to DIN 11902: the achievable ironing performance depends on overall conditions such as, for example, the type of laundry and the experience of the operator.

#### Material number: 11741260

| Construction type and version                              |                                         |
|------------------------------------------------------------|-----------------------------------------|
| Construction type                                          | Laundry infeed and outfeed at the front |
| Can be set up against a wall                               | •                                       |
| Range                                                      | Professional                            |
| Outer casing                                               | Iron grey                               |
| Roller diameter in mm                                      | 210                                     |
| Working width in mm                                        | 1000                                    |
| Heater plate material                                      | Aluminium                               |
| Padding                                                    | Supple steel wool                       |
| Ironer cover                                               | ARAMID needle-felt cloth                |
| Application                                                |                                         |
| Suitable for the hotel and catering industry               | •                                       |
| Suitable for retirement and care homes                     | •                                       |
| Suitable for laundrettes                                   | •                                       |
| Suitable for residential homes and apartments              | •                                       |
| Suitable for hospitals                                     | •                                       |
| Suitable for offshore use                                  | •                                       |
| Suitable for marine use                                    | •                                       |
| Suitable for camp sites                                    | •                                       |
| Suitable for domestic use                                  | •                                       |
| Performance data                                           |                                         |
| Max. ironing performance at 15 % residual moisture in kg/h | 30.0                                    |
| Tested operating hours                                     | 20000                                   |
| Control system                                             |                                         |
| Control system                                             | Touch display                           |
| Touch display (optional)                                   | Touch-Display PRI                       |
| Programme setting                                          | Setting of defined programme parameters |
| Minimum ironing speed, controlled in m/min                 | 1.5                                     |
| Maximum ironing speed, controlled in m/min                 | 4.0                                     |
| Adjustable temperature                                     | Infinitely variable                     |
| Standard electrical connection                             |                                         |
| Heating type                                               | Electric                                |
| Electrical connection                                      | 3N AC 400V 50-60HZ                      |
| Electric heater rating in kW                               | 4.50                                    |
| Total connected load in kW                                 | 5.00                                    |
| Fuse rating in A                                           | 16                                      |
| Dimensions and weight                                      |                                         |
| External dimensions, height in mm                          | 1032                                    |
| External dimensions, width in mm                           | 1579                                    |
| External dimensions, depth in mm                           | 476                                     |
| External dimensions, gross height in mm                    | 1374                                    |
| External dimensions, gross width in mm                     | 1763                                    |
| External dimensions, gross depth in mm                     | 660                                     |
| Net weight in kg                                           | 122                                     |
| Gross weight in kg                                         | 136                                     |
| Maximum floor load in N/m <sup>2</sup>                     | 1220                                    |
| Emissions data                                             |                                         |
| Emission sound pressure level in the workplace             | <70 dB(A) re 20 µPa                     |



## PRI 210 [EL STW AB]

Rotary ironer, electrically heated

With the latest controls and flexible working height.



### Material number: 11741260

Heat dissipation into the room in MJ/h 4.50

#### Features

|                                                                          |   |
|--------------------------------------------------------------------------|---|
| Automatic finger guard                                                   | • |
| FlexControl footswitch                                                   | • |
| Airing bar                                                               | • |
| Feed-in board                                                            | • |
| Pick-off bands                                                           | • |
| Laundry box (optional)                                                   | • |
| Laundry return feed                                                      | • |
| Favourite programme                                                      | • |
| Incorrect feed recognition                                               | • |
| Air suspension                                                           | • |
| Pause function                                                           | • |
| High contact pressure                                                    | • |
| Clean and wax heater plate indicator (op                                 | • |
| Plinth (optional)                                                        | • |
| Option of ironing when seated                                            | • |
| APRI 319 care set for the heater plate included in the scope of delivery | • |

Machine-independent accessories

#### Connection options

|                                     |   |
|-------------------------------------|---|
| Payment system (optional)           | • |
| Peak load cut-out/energy management | • |

#### Standards, test certificates and symbols

|                                              |   |
|----------------------------------------------|---|
| VDE                                          | • |
| CE                                           | • |
| EAC                                          | • |
| WEEE                                         | • |
| VDE-EMC                                      | • |
| RCM                                          | • |
| Splash-proof IPX0                            | • |
| UKCA                                         | • |
| Complies with Machinery Directive 2006/42/EC | • |