

COMBI-STEAMER CUCINA 2011QT- PRO

SALCS550500



PRODUCT FEATURES

- High-resolution TFT colour touch screen, fully integrated in the hygienic glass panel

Easy, understandable **user interface** - controls and display in one place.

Temperature, humidity, time and core temperature can be changed with the scrollbar or the ten-key keypad

Temperature can be adjusted to nearest degree from 30 °C up to 250° C, humidity from 0 to 100%.

Active climate - dry and moist heat with active moistening and dehumidification in any combination

Inherent moisture control at 5 levels in hot air environment

Special programs: Low-temperature cooking, Softcooking, Cook and Hold - for slow-cooking from 30 °C to 120 °C.

The **CombiStep function** allows you to combine up to 20 different cooking steps, which are clearly displayed in the cooking steps overview.

EcoMode to optimise power consumption of cooking processes, such as slow-cooking and stewing

5 ventilator speeds plus interval mode for perfect, uniform cooking and baking results.

Highly effective **ventilator with auto-reverse** and interval mode for gentle cooking.

Temp active - automatic preheating or cooling down to preset temperature.

Cool down function with motor control when door is open for efficient climate control.

Start time pre-set and E/2 function (energy saving function).

Automatic quantity adjustment (AQA).

Cooking chamber safety steam extraction (SDA)

Manual steam injection - for custom addition of moisture e.g. for baking.

Time setting from 1 minute to 24 hours, continuous operation and start time pre-setting up to 24 hours in real-time.

Start from any phase for multi-phase cooking processes for greater convenience

Core temperature regulation with multi-point sensor - to accurately measure the core temperature from 0 °C to 99° C; control cooking processes with warning if failed to insert probe.

Data exchange via USB.

TECHNICAL SPECIFICATIONS

Model	LxDxH (mm)	Weight (kg)	Capacity (GN 1/1)	Plates (Ø32cm)	Power (kW)	Spacing (mm)	Water Connection (G 3/4 A)	Electrical Connection
SALCS550500	1115x875x1925	360	20	80	34.6 - 44	67	2 x G	400V/ 1 ph/ 50-60Hz