

UPRIGHT FREEZER: REACH-IN

INF-AGB701BT



PRODUCT FEATURES

high quality meals at any time pleasing both the customer, food safety on all your dishes as the chilling process fully conforms to the HACCP regulations, and save time by up to 30% by preparing meals in batches. Doors are equipped with hinges for automatic return and permanent pressure during closing. Higher precision in managing temperature settings with the new intuitive digital controller. Greater ability to adjust of temperature ranges as per the end user's requirement. All condenser units are tested 100%, in helium chambers to refrigerant leak detections. AENOR audited and certified by internationally recognized firm. ISO 9001:2015 (Quality); ISO 14001:2015 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety). Audited and Certified by INTERTEK for compliance with UL 471 and NSF7.

Exterior: AISI 304 Stainless Steel. Compliant with HACCP regulations. Constructed following EC and HACCP regulations

Interior: AISI 304 Stainless Steel. Drain inside the cabinet. Sealed interior floors and rounded cabinet corners. Includes a heated conical probe which is easy to use and remove.

Insulation: CFC-Free polyurethane insulation, entire cabinet structure is foamed-in place using a high density polyurethane insulation. Low GWP & Zero ODP effect.

Control: USB connection, to upload/download of the configuration parameters, programs and download the information relative to the HACCP alarms. It is possible to customize and memorise programmes.

Doors: Self closing door with stay open feature. Integrated handle and blocked hinge. Stamped interior of door with a triple chamber door gasket easy to remove. Possibility of changing the opening direction of the doors. Heated door structure to avoid accumulation of ice.

Refrigeration: Blast chilling: +90°C to +3°C in less than 90 minutes, Blast freezing: +90°C to -18°C in less than 270 minutes, Expansion valve and defrost by compressor stop. System of Ventilated Condensation. System of Forced Evaporation. Evaporator coil coated with anti-corrosion polyester epoxy

TECHNICAL SPECIFICATIONS

Model	LxDxH (mm)	Door	Shelves Included	Temp. Range (°C)	Capacity (L)	Power (KW)	Consumption (kWh/24h)	Electrical Connection
INF-AGB701BT	687x794x2130	1	3	-18	560	0.63	7.80	230V/ 1 ph/ 50Hz