

ROLL-IN 20 PAN BLAST CHILLER WITH BUILT IN CONDENSING UNIT

INFABT201CBI



The images shown are for illustration purposes only and may not be an exact representation of the product

PRODUCT FEATURES

Doors

- Polyurethane insulated door.
- Self-closing door with stay open feature.
- Heavy-duty hinges with horizontal and vertical adjustment.
- Triple chamber snap in door gaskets for easy removal and cleaning.
- Heated door frame to avoid accumulation of ice.

Refrigeration

- Control panel with an easy to read screen and menu.
- Manual defrost during cycles and automatic defrost during maintenance.
- Evaporator coil coated with anti – corrosion material
- 100% polyester.
- Forced air refrigeration system.
- Blast chilling: + 149 °F (65 °C) to + 37°F (3°C) in less than 90 minutes.
- Blast freezing: +149 °F (65 °C) to 0°F (-18 °C) in less than 4 hours

Interior

- AISI 304 Stainless Steel.
- Sealed interior floors and rounded cabinet corners.
- Includes an easy to use heated conical product probe.

TECHNICAL SPECIFICATIONS

Model	Dimensions (WxDxH))	Capacity (Lt)	Temperatre range	Electrical
ABT201CBI	1200x1095x2465	1704	+3°C/ -40°C	220V/3ph/60Hz